



35kV cabinet top busbar number

Lightweight, durably-constructed fiberglass primary sectionalizing cabinets are manufactured with our spray-up/lay-up process and are available in multiple sizes and designs for ...

Bolted connection is insensitive to cabinet height errors, ideal for retrofit projects. Complete Component Set Includes Type C bushing (206), Type C tee connector (ACD), Type C cross connector (ACS), ...

The maximum mains rating, bus bar rating, load center cover number, lug torque data, and short circuit current rating will be located on the box label of the load centers. The box label is ...

Top-hinge design for easy access to all electrical components. All-welded construction. padlock provision standard on all models for tamper resistance. Two provisions for added security

The cabinets shall be equipped with a hinged cabinet top to facilitate entry to the cable compartments; it shall open approximately 60 degrees and have door stays to hold it in the open position.

Available in sizes for use on single and three-phase systems rated 200A or 600A, 15kV through 35kV. Top-hinge design for easy access to all electrical components. All-welded construction.

Provides a safe and convenient primary cable terminating, sectionalizing, tapping, and switching point for underground distribution systems.

Junction bars and sectionalizing cabinets provide an extremely compact, versatile solution for loop, tap, grounding, testing or sectionalizing applications through 35kV, 900A.

Provides an extremely compact, versatile solution for loop, tap, grounding, testing or sectionalizing applications through 35kV, 900A. Padmount, vault and subsurface designs are available.

For all metering installations (secondary, 15kV, 25kV, & 35kV), refer to Section AOJ in the APCO Company Specific Section of the Southern Company Overhead Distribution Standards.

Web: <https://www.maxtools.co.za>

